



Specifications Philips Coreline SlimDownlight LED  
DN135B 4000K 2000lm | Cool White

[View Product](#)

General Information

|                          |                          |
|--------------------------|--------------------------|
| SKU                      | 233802                   |
| EAN                      | 8718699389246            |
| Brand                    | Philips                  |
| Manufacturer Name        | DN135B LED20S/840 IA1 WH |
| Any Lamp all-in warranty | 5 Years                  |
| Average Lifetime (h)     | 50000                    |

Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tilttable                   | No                |
| Technology                  | LED Integrated    |
| Wattage                     | 27                |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Dimmable          |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Driver Included             | Yes               |

|                          |                          |
|--------------------------|--------------------------|
| Beam Angle (degree)      | 120                      |
| Luminous Flux (Lumen)    | 2100                     |
| Luminous Efficacy (lm/W) | 74.1                     |
| Power factor             | >0.90                    |
| Unified Glare Rating     | < 22 - for general areas |
| Optical Cover            | PC (Polycarbonate)       |
| Finish of Reflector      | PC (Polycarbonate)       |
| Product Type Category    | LED Downlight            |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 200                           |
| IP-rating              | IP44                          |
| Impact Protection (IK) | IK02 - 0.20 joule             |
| Operating Temperature  | -20 to +35                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Colour of material     | White                         |
| Fixture Connection     | PI [Push-in connector 3-pole] |
| Series                 | DN135B                        |

## Dimensions

Height (mm)

**Why Any-lamp?**

23

Diameter (mm)

215



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

Type of sensor

No Sensor

