



**Specifications Philips LED Panel  
CoreLine RC132V 40W 4300lm - 840  
Cool White | 60x60cm - UGR <19 - Dali  
Dimmable**

[View Product](#)

## General Information

|                          |  |
|--------------------------|--|
| SKU                      | 246030                                   |
| EAN                      | 8720169013711                            |
| Brand                    | Philips                                  |
| Manufacturer Name        | RC132V G5 31_36_43S/840 PSD W60L60OCELB3 |
| Any Lamp all-in warranty | 5 Years                                  |
| Average Lifetime (h)     | 50000                                    |
| Series                   | RC132V                                   |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 40                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Light Distribution          | Symmetrical        |

|                          |                               |
|--------------------------|-------------------------------|
| Luminous Flux (Lumen)    | 4300                          |
| Luminous Efficacy (lm/W) | 116                           |
| IP-rating                | IP44                          |
| Impact Protection (IK)   | IK03 - 0.35 joule             |
| Fixture Connection       | PI [Push-in connector 6-pole] |
| Driver Included          | Yes                           |
| Power factor             | >0.90                         |
| Product Type Category    | LED Panel                     |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | 3H Emergency Light             |
| Colour of the Fixture | White                          |
| Housing               | Steel                          |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 16      |

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

**Sensor Information**  **Up to 7 years warranty**  **Easy return process**

Type of sensor No Sensor

